

PC-3200M/C



CHARGER SPECIFICATIONS

Model No: PC-3200M/C	NSN: TBD
Manufacturers CAGE Code: 03UN7	
AC Input Range: 90 to 264VAC; 47 to 63Hz	
Battery Charge Voltage: 8.4VDC to 16.8VDC max. per position	
Battery Charge Current: 3A max. per position	
Communication: SMBus spec v2.0; SBC v1.1, Level 3 smart charger	
Battery Connection: Pogo pins for charge and SMBus contacts	
Led Indicators: Flashing green LED – Charging Solid green LED – Fully Charged Flashing red LED – Error Solid red LED – Waiting for Charging to Start	
Weight: 112 lbs. (51 Kg)	
Dimensions: Closed 31"L x 31"W x 29"H (79cm x 79cm x 74cm) Open 31"L x 31"W x 47"H (79cm x 79cm x 120cm)	
Operating / Charging Temp: 0° C to 50° C (32°F to 122°F)	
Storage Temp: -25° C to 70° C (-13°F to 158°F)	
Humidity: 95% relative	
Color: Black	
Exterior Carrying Case: Hard plastic case	
Charger Housing: Aluminum	
Harmonized Tariff Code: 8507.90.80.00	

APPLICATIONS

- Bulk charging for depot and field settings

KEY FEATURES

- Smart charger – level 3
- LED display for each battery charging position
- 32-position battery charging capability
- Unattended charging
- Ruggedized environment resistant case

BENEFITS

- Charges up to 16 batteries simultaneously – FIFO protocol
- Battery and charger communicate for optimum charging efficiency, battery life and safety
- Easy battery connection – no cables required
- Batteries contained in charger for charge cycle duration

CHARGES THE FOLLOWING BATTERIES

- PB-LW-01, PB-LW-01-NC, PB-LW-02, PB-LW-03, PB-LW-04, PB-LW-05, PB-LW-06, PB-LW-07, PB-LW-08

Note: specify battery model number at time of purchase